C.S.I.Consulting-Service Innovation
+39.3496713382 - lino@callserviceitalia.com

SK30

SK30 DTF PRINTER

MAX SPEED

4㎡/h

24-HOUR SERVICE

AUTO CLEANING

HIGH PERFORMANCE

HIGH STABILITY

ORIGINAL HEAD

HIGH PRECISION

TECHNICAL PARAMETERS

Model	SK30
Printhead	Type: EPSON F1080 Quantity: 2
Print Speed	6PASS: 4㎡/h 8PASS: 3㎡/h
Ink Type	Pigment Ink
Print Color	CMYK+W
Print Width	300mm
Power	1000W 220V/110V 50Hz/60Hz 10A
Weight	N.W.: 85kg G.W.: 110kg
Print Interface	Gigabit Port
Print Media	PET Film
Image Format	JPG, TIF, PDF, etc.
System Configuration	WIN7 and Above
Work Environment	Temp.: 15℃~30℃ Humidity: 35%~65%
RIP Software	Riin(Standard); Maintop, CADlink(Fiery), FlexiPRINT(Optional), etc.
Size	Machine Size: 1150*700*500mm Package Size: 1200*650*620mm

*The technical indicators and content of the machines are subject to the actual sales of the machine. The technical parameters and content of this brochure will be changed without further notice. The right of interpretation belongs to the manufacturer.

FUNCTIONS AND FEATURES

ORIGINAL EPSON PRINTHEAD

Equipped with double F1080 printheads, higher printing speed.



SILENT LINEAR GUIDE RAIL

No noise, more smooth movement, more stable printing, longer service life of the machine.

LEADSHINE BRUSHLESS INTEGRATED MOTOR

Feeding media more accurate,and graphic output is more stable.

AUTOMATIC AIR SUCTION SYSTEM

Three-section heating design, more stable printing, and the film runs smoother.

WHITE INK AUTOMATIC MIXING/CIRCULATION

Anti-clogging and anti-precipitation, more uniform ink output.

EASY OPERATION

Equipped with LCD panel, easier operation.

APPLICATIONS